

## Dishwasher 50x50 - electronic control

231753

Extremely easy to use, clean and service. Ideal for cleaning plates, cutlery, glassware, cups, trays. Electronic controls. Detergent and rinse aid dispensers and pump standard included. Housing made of stainless steel AISI 304. Rotating plastic washing and stainless steel rinsing arms at the bottom of the chamber. Stationary plastic washing arms and rotating stainless steel rinse arms at the top of the chamber. Robust double-skinned door fitted with a microswitch, stops the program when opened. Maximum height of glasses: 325 mm. Maximum height of plates: 335 mm. Water temperature during washing: 60°C. Water temperature during rinsing: 85°C. Boiler (capacity/power): 6L / 6 kW Bath (capacity/power): 35L / 2.8 kW. Washing pump: 0,75 kW. Safety thermostat for boiler/bath: up to 105°C / 99°C. Electronic water thermometer for boiler and tank. Sealing factor of the pump: IP 44 ø40 mm feet, ≈10 mm in height adjustable Weight: 55 kg. FUNCTIONS: Three washing programs: 60, 120, 180 s. (The washing program will be automatically extended with the time needed for warming up the rinsing water to +85°C) Dishwasher chamber cleaning program. Cold rinse function - ideal for glass washing. THERMO-PROTECTOR system to prevent cold water flushing - guarantees the rinsing won't start till the temperature is 85°C. SOFT START system starts the water pump at a low level pressure and gradually increases the pressure to protect delicate items. 8-point self-diagnostic system. ECO system - for reduced power consumption. BENEFITS OF COLD RINSE: Cools down the glasses after cleaning, making them ready for use immediately. Removes the smell of rinse aid, ideal for wine glasses. EQUIPMENT: 1 universal glass basket 500x500x(H)105 mm. 1 basket with pins for deep and shallow plates with 5x8 pcs, 500x500x(H)105 mm. 1 cutlery basket 110x110x(H)130 mm. Electric detergent and rinse aid dispenser. Water hose 1.5 m long, with 3/4 female thread connection. Drain pump and drain hose. Power cord without plug.

### Specifications

Usage area	: Kitchen
Voltage	: 400
Marketing Packed per	: 1
Length (mm)	: 570
Width (mm)	: 600
Height (mm)	: 830
Power (input) (W)	: 6600
Control panel	: Digital
Programmable	: Yes
Drain tap	: Yes
Measurements	: 570x600x(H)830



### Transport specifications

EAN	: 8711369231753
Intrastat code	: 84221900
Gross weight (kg)	: 60
Net weight (kg)	: 53
Sales units per pallet	: 2
Plastic packaging (gram)	: 265

#### HENDI B.V.

Innovatielaan 6  
6745 XW De Klomp, The Netherlands  
T: +31 (0)317 681 040  
E: info@hendi.eu

#### HENDI Polska Sp. z o.o.

ul. Firmowa 12  
62-023 Robakowo, Poland  
T: +48 61 6587000  
E: info@hendi.pl

#### HENDI GmbH

Ehring 15  
5112 Lamprechtshausen, Austria  
T: +43 (0) 6274 200 10 0  
E: office.austria@hendi.eu

#### HENDI S.R.L.

Str. 13 decembrie 94A, Hala 14  
Braşov, 500164, Romania  
T: +40 268 320330  
E: office@hendi.ro

#### PKS HENDI South East Europe SA

5 Metsovou Str.  
18346 Moschato, Athens, Greece  
T: +30 210 4839700  
E: info@pks-hendi.com

#### HENDI Italia S.R.L.

Via Leonardo da Vinci 4  
39100 Bolzano (BZ), Italy  
T: 800 727 438  
E: office.italy@hendi.eu